



DIANAMIC® Abrasive Products Inc.
2566 Industrial Row • Troy, Michigan 48084, USA

Single Layer / Electroplated Superabrasive Grinding Wheel Specification Questionnaire

Thank you for your request for a Single Layer also known commonly as an electroplated or galvanic superabrasive grinding wheel. The following questions should be answered as completely as possible. Your response will allow us to design and manufacture the appropriate **“application oriented”** superabrasive grinding wheel best suited to your specific requirements and environment.

If you are currently using a superabrasive Single Layer grinding wheel, please provide the current wheel specifications and the manufacturers’ name. This information will allow us to cross reference your current product to the Dianamic **“application oriented”** products we manufacture.

Often times the type of grinding wheel you are currently using is not the best for your specific application. We will analyze the information you provide us concerning the type of product you are grinding as well as the grinding environment and recommend the appropriate **“application oriented”** bond system and mesh / micron size for your specific micro finish requirements.

When evaluating competitive products and quotes; please note that often times Dianamic is not the least expensive supplier, although we are the highest quality supplier. Keep in mind that we use in our manufacturing processes only the highest quality available ingredients and chemicals, and never use any reclaim or mixed product. We use only Virgin Diamond (synthetic and natural) and various types of cBN which are selected on an **“application oriented”** basis.

What is **“application oriented”** superabrasive grinding wheel? Since 1985 till now, Dianamic selects not only the highest quality Diamond and cBN but also selects the most appropriate type of superabrasive to be used on an application case by case basis, based on customer requirements and specifications.

Not all Diamond and cBN is created equal. Each type of superabrasive has very specific ways it reacts during the machining / grind process our selection process for the **“application oriented”** is based on 28+ years of actual manufacturing experience.



DIANAMIC® Abrasive Products Inc.
2566 Industrial Row • Troy, Michigan 48084, USA

Single Layer / Electroplated Superabrasive Grinding Wheel Specification Questionnaire
Please answer questions as completely as possible

Company Name _____

Ship to Address _____

Bill to Address if different _____

City _____ State / Province _____

Zip Code / Postal Code _____ Country _____

Telephone _____ Facsimile _____

Company Web site _____

Contact Name _____

Contact Email _____

Contact Telephone and Extension and Facsimile if different from Company _____

Superabrasive Grinding Wheel Specifications in Inches or Metric
submit wheel and or part prints in AutoCAD or PDF format to info@dianamic.com

1. Grinding Wheel Shape (if available) _____
(For mountable OD type wheels)

2. ID Style Grinding Wheels- Head Diameter _____ Head Length _____

Shank Size _____ OAL _____ Other _____

3. Bond Type

SINGLE LAYER / ELECTROPLATED BRAZED
(For Resin, Metal or Vitrified bonds, please fill out the Bonded Questionnaire)

4. Current Supplier's Name / Manufacturers Name _____

5. OD or Form Wheel size specifications

a. Diameter _____

b. Thickness _____



DIANAMIC® Abrasive Products Inc.
2566 Industrial Row • Troy, Michigan 48084, USA

Single Layer / Electroplated Superabrasive Grinding Wheel Specification Questionnaire
Please answer questions as completely as possible

c. Bore Diameter _____ Expected Tolerance + or - _____

d. Bolt Hole Circle if applicable _____

e. Mounting Hole thread size and pattern if applicable _____

f. Mesh Size or Micron Size _____

g. Superabrasive Type (please circle)

Natural Diamond Synthetic Diamond cBN

If you know if the Synthetic Diamond is Crystalline (which offers a more uniform shape and size controlled crystal) or Non Crystalline (which is a free cutting crystal), please list below:

h. Any additional information that may be useful, please describe: _____

i. If you do not have the wheel shape, please describe as completely as possible, include any angle / angles; radius / radii or any form per print specifications that can be dressed. Advise if there are any hub on either or both sides and diameter and thickness or if the wheels are to be mounted on standard Sopko adaptors or other type of wheel adaptor.



DIANAMIC® Abrasive Products Inc.
 2566 Industrial Row • Troy, Michigan 48084, USA

Single Layer / Electroplated Superabrasive Grinding Wheel Specification Questionnaire
Please answer questions as completely as possible
Product being ground

Steel Grade _____ Rockwell Hardness C _____

Carbide Grade and Cobalt content _____

Ceramic Type and Grade _____

Friction Material type _____

Glass or other type of material _____

Machine, Coolant and Filtration Specifications

Type of machine used and brand name _____

Spindle HP / KW _____ Is spindle constant velocity YES or NO

Coolant use and type _____ Is a coolant chiller used YES or NO

Filtration type and to what micron filtered _____

Do you have high pressure coolant velocity system? YES or NO

Type, brand, flow rate, velocity, pressure, temperature _____

Grinding Parameters

Type of grinding
 OD ID SURFACE FORM CNC CREEP FEED HEDGE GRIND PROFILE OPG OTHER
 (Please circle)

In feed depth _____ Cross feed speed _____

Spindle speed _____ RPM /SFM _____ Variable speed YES or NO

Stock removal per pass _____ Total Stock Removal _____

Size of part being ground _____