

## **Superabrasive Bonded Grinding Wheel Specification Questionnaire**

The following questions should be answered as completely as possible. Your response will allow us to design and manufacture an "application oriented" Superabrasive grinding wheel best suited to your specific requirements and environment.

If you are currently using a superabrasive bonded grinding wheel, please provide the current type of bond and wheel specifications which are always located on the grinding wheel and the packaging as well as the manufacturers' name. This information will allow us to cross reference your current product to the Dianamic "application oriented" Superabrasive bonded products.

Often times the type of grinding wheel you are currently using is not the best for your specific application. We will analyze the information you provide us concerning the type of product you are grinding as well as the grinding environment and recommend the appropriate "application oriented" bond system and mesh / micron size for your specific micro finish requirements.

When evaluating competitive products and quotes; please note that often times Dianamic is not the least expensive supplier, although we are the highest quality supplier. Keep in mind that we use in our manufacturing processes only the highest quality available ingredients in our bond systems and never use any reclaim or mixed product (Diamond or cBN). We use only Virgin Diamond (synthetic and natural) and various types of cBN which are selected on an "application oriented" basis.

What is "application oriented" superabrasive grinding wheel? Since 1985, Dianamic selects not only the highest quality Diamond and cBN, but also selects the most appropriate type of superabrasive to be used on an application case by case basis, based on customer requirements and specifications.

Not all Diamond and cBN is created equal. Each type of superabrasive has very specific ways it reacts during grinding / machining processes. Our selection process for the "application oriented" is based on 29+ years of actual manufacturing experience.



## Superabrasive Bonded Grinding Wheel Specification Questionnaire Please answer questions as completely as possible

Compar	y name							
Ship to	Address							
Bill to A	ddress if different							
	State / Province							
Zip Cod	e / Postal CodeCountry							
Telepho	neFacsimile							
Company Web site								
Contact Name								
Contact Email								
Contact Telephone and Extension and Facsimile if different from Company								
Superabrasive Grinding Wheel Specifications in Inches or Metric or submit wheel prints in AutoCAD to <a href="mailto:info@dianamic.com">info@dianamic.com</a>								
1.	Grinding Wheel Shape (if available)  (For mountable OD type wheels)							
2.	D Style Grinding Wheels- Head DiameterHead Length							
	hank SizeOALOther							
3.								
4.	Sond specifications (Bond specifications can be found on your existing grinding wheel or packaging)							
i	. Diameter							
	o. Thickness							



## Superabrasive Bonded Grinding Wheel Specification Questionnaire Please answer questions as completely as possible

С.	Bore DiameterExpected Tolerance or +							
d.	Bolt Hole Circle if applicable							
е.	Mounting Hole thread size and pattern if applicable							
f.	Bond Depth							
g.	Mesh Size or Micron Size							
ո.	Superabrasive Type (please circle)							
	Natural Diamond Synthetic Diamond cBN							
	If you know if the Synthetic Diamond is Crystalline (which offers a more uniform shape and size controlled crystal) or Non Crystalline (which is a free cuttin crystal), please list below:							
If you know what type of superabrasive by manufactures name and any subsequent coating such as Nickel, Copper, Chromium, Copp Bronze and Cobalt, Silicon Based or Titanium, please list below:								
	Any additional information that may be useful, please describe:							
. If you do not have the wheel shape, please describe as completely as possib include any angle / angles; radius / radii or any form per print specifications that can be dressed. Advise if there are any hub on either or both sides and diameter at thickness or if the wheels are to be mounted on standard Sopko adaptors.								



## **Product being ground**

Steel Grade	Rockwell Hardness C					
Carbide Grade and Cobalt (	ontent					
Ceramic Grade						
Friction Material type						
Glass or other type of mate	erial					
Mach	nine, Coolant and F	iltration Specif	ications			
Type of machine used and	brand name					
Spindle HP / KW		Is spindl	Is spindle constant velocity YES or NO			
Coolant use and type		ls a	coolant chille	er used	d YES or NO	
Filtration type and to what	micron filtered					
Do you have high pressure	coolant velocity syste	m? YES or NO				
Type, brand, flow rate, velo	ocity, pressure, tempe	rature				
	<u> </u>					
Grin	ding Parameters –	Type of Grind	Process			
OD ID SURFACE FORM	1 CNC CREEP FEED (Please circ		PROFILE	OPG	OTHER	
In feed depth		Cross feed speed				
Spindle speed	RPM /SFM		Variable	speed	YES or NO	
Stock removal per pass		Total Stock Rei	moval			
Size of part being ground_						
Dresser type						

Copyright Dianamic Abrasive Products, Inc. 1985-2023